

POLYMER DOCKLITE® HEADS

Polymer Docklite Light Heads



DLP-INC-LH



DLP-40SBFL-LH

DESCRIPTION: Polymer Docklite® heads are made with a heat-resistant polymer accommodating incandescent lamps up to 250 watts and self-ballasted compact fluorescent lamps. Lamp stabilization features provide increased impact resistance to maximize lamp life and minimize maintenance requirements. Can be used with Single-Strut, Double-Strut and Spring Arms.

SPECIFICATIONS

Light Head Construction: Robust high temperature polymer housing resists denting, deflection, and wear.

Lamp Type and Wattage: Incandescent model accommodates up to 250 watt lamps. ENERGY STAR® qualified 40 watt self-ballasted compact fluorescent lamp included with fluorescent model.

Heat Shield: Metal shield on the incandescent model deflects heat, keeping the head cooler to the touch.

Hardware: Zinc-plated steel hardware resists corrosion.

Plug: Recessed 3-prong IEC type plug fits directly into arm receptacle.

Modular Arm Construction: (order separately) 1-1/2" square steel tube arms available in four lengths (24", 42", 60" and 90"). Wrist action zinc plated steel joint on single-strut arms 42" and longer. Washers at all bracket joints for smooth operation, greater stability, and longer wear. Thermoset powder-coated safety yellow finish resists wear.

Cord: Wear-resistant, 3-conductor AC cord from arm fits directly into standard outlet. Male plug on light head cord plugs into female receptacle in arm.

Mounting Bracket: Bracket is 3/16" thick and 3" x 5" zinc plated steel.

Lamp Support: Spring loaded socket assembly on incandescent head draws lamp into housing for better protection and support and pushes outward for easy lamp removal. Fluorescent model also contains a lamp stabilization feature.

COMPLIANCES

UL153 Listed: Suitable for Dry Location

cUL Listed: Indoor



PHOENIX®

ORDERING INFORMATION

Polymer Light Head Model Numbers

Lamp included with fluorescent model.

SERIES		WATTAGE/TYPE		PART
DLP	—	INC	—	LH
DLP	—	40SBFL	—	LH

Steel head also available. Please contact factory.

3 year limited warranty

Modular Arms Model Number

Single-strut arms are standard.

SERIES	LENGTH	PART	ARM
DL	42	ARM	DS
DL	24: 24"	ARM	DS: Double-strut ¹
	42: 42"		SP: Spring Arm ²
	60: 60"		
	90: 90"		

¹ Double-strut arms available in 42" and 60" lengths only.

² Not available in 90" length. Double-Strut Spring arms also available.

ACCESSORIES

Ordered separately for field installation.



DL-18-FAN

Model	Description	P/N
DL-18-FAN	18" 3-Speed Docklite Fan (use only w/ double strut arms)	1860830
SS-1	Swing Stop Kit	1150900
WB-22	Adjustable Wall Bracket	1150300
Lamp (40SBFL)	40 watt Self-ballasted Compact Fluorescent Lamp (replacement)	4220131

N-5610918C